

## Technical data sheet

### Connection unit

Part no.: 50131259

ME 348 104

#### Contents

- Technical data
- Electrical connection
- Operation and display



Figure can vary

## Technical data

### Basic data

Suitable for	BCL 348i
Suitable for interface	PROFINET

### Connection

Number of connections	5 Piece(s)
-----------------------	------------

#### Connection 1

Function	PWR / SW IN / OUT
Type of connection	Cable with connector
Cable length	900 mm
Thread size	M12
Type	Male
Material	Metal
No. of pins	5 -pin
Encoding	A-coded

#### Connection 2

Function	Service interface
Type of connection	USB

#### Connection 3

Function	HOST / BUS IN
Type of connection	Cable with connector
Cable length	500 mm
Thread size	M12
Type	Female
Material	Metal
No. of pins	4 -pin
Encoding	D-coded

#### Connection 4

Function	BUS OUT
Type of connection	Cable with connector
Cable length	700 mm
Thread size	M12
Type	Female
Material	Metal
No. of pins	4 -pin
Encoding	D-coded

#### Connection 5

Function	Signal OUT
Type of connection	Cable with connector
Thread size	M8
Type	Female
Material	Metal
No. of pins	4 -pin
Encoding	A-coded

### Mechanical data

Design	Cubic
Dimension (W x H x L)	64 mm x 33.5 mm x 43.5 mm
Housing material	Metal
Net weight	70 g
Housing color	Red, RAL 3000

### Operation and display

Type of display	LED
Number of LEDs	2 Piece(s)

### Classification

Customs tariff number	84733080
eCl@ss 5.1.4	27280190
eCl@ss 8.0	27280190
eCl@ss 9.0	27279090
eCl@ss 10.0	27280192
eCl@ss 11.0	27280191
ETIM 5.0	EC002498
ETIM 6.0	EC003015
ETIM 7.0	EC003015

## Electrical connection

### Connection 1

Function	PWR / SW IN / OUT
Type of connection	Cable with connector
Cable length	900 mm
Cable color	Black
Wire cross section	0.34 mm <sup>2</sup>
Thread size	M12
Type	Male
Material	Metal
No. of pins	5 -pin
Encoding	A-coded

# Electrical connection

## Pin Pin assignment

1	VIN
2	SWIO 1
3	GNDIN
4	SWIO 2
5	FE

## Connection 2

Function	Service interface
Type of connection	USB
Connector type	USB 2.0 Mini-B

## Connection 3

Function	HOST / BUS IN
Type of connection	Cable with connector
Cable length	500 mm
Sheathing material	PUR
Cable color	Green
Wire cross section	0.34 mm <sup>2</sup>
Thread size	M12
Type	Female
Material	Metal
No. of pins	4 -pin
Encoding	D-coded

## Pin Pin assignment

1	TD+
2	RD+
3	TD-
4	RD-

## Connection 4

Function	BUS OUT
Type of connection	Cable with connector
Wire cross section	0.34 mm <sup>2</sup>
Cable color	Green
Cable length	700 mm
Sheathing material	PUR
Thread size	M12
Type	Female
Material	Metal
No. of pins	4 -pin
Encoding	D-coded

## Pin Pin assignment

1	TD+
2	RD+
3	TD-
4	RD-

# Electrical connection

## Connection 5

Function	Signal OUT
Type of connection	Cable with connector
Thread size	M8
Type	Female
Material	Metal
No. of pins	4 -pin
Encoding	A-coded
Wire cross section	0.34
Cable color	Black
Cable length	2,000
Sheathing material	PUR

Pin	Pin assignment
1	V+
2	n.c.
3	GND
4	SW OUT

# Operation and display

LED	Display	Meaning
1	Green, continuous light	Ethernet
	Yellow, flashing	Data transmission active
2	Green, continuous light	Ethernet
	Yellow, flashing	Data transmission active