

## Technical data sheet

### Adapter

Part no.: 50134904

KDS U-M8-4A-M8-3A-P1-000

#### Contents

- Technical data
- Electrical connection
- Accessories



Figure can vary



## Technical data

### Electrical data

#### Performance data

Operating voltage Max. 50 V AC / 60 V DC

### Connection

#### Connection 1

Type of connection Connector

Thread size M8

Type Female

No. of pins 4 -pin

Version Axial

#### Connection 2

Type of connection Connector

Thread size M8

Type Male

No. of pins 3 -pin

Version Axial

#### Cable properties

Shielded No

### Mechanical data

Width across flats 9 mm

Material PUR

### Certifications

Degree of protection IP 67

### Classification

Customs tariff number 85366990

eCl@ss 5.1.4 27279201

eCl@ss 8.0 27440104

eCl@ss 9.0 27069190

eCl@ss 10.0 27440106

eCl@ss 11.0 27440106

ETIM 5.0 EC002498

ETIM 6.0 EC002498

ETIM 7.0 EC002925

## Electrical connection

### Connection 1

Type of connection Connector

Thread size M8

Type Female

No. of pins 4 -pin

Version Axial

### Connection 2

Type of connection Connector

Thread size M8


Type Male

No. of pins 3 -pin

Version Axial

## Accessories

### General

	Part no.	Designation	Article	Description
	50132266	TT-Set 0,6-13	Tool	Type: Torque key Width across flats: 13 mm Torque: 0.6 N·m Material: Plastic, Stainless steel Ambient temperature: -40 ... 120 °C

## Accessories

### Note



🔗 A list with all available accessories can be found on the Leuze website in the Download tab of the article detailed page.