

## Technical data sheet

### Wireless mobile 2D-code reader

Part no.: 50122434

IT 1911i ER-3

#### Contents

- Technical data
- Electrical connection
- Operation and display
- Notes
- Accessories



Figure can vary



## Technical data

### Basic data

|        |        |
|--------|--------|
| Series | IT19xx |
|--------|--------|

### Read data

|                      |                             |
|----------------------|-----------------------------|
| Code types, readable | 2/5 Interleaved             |
|                      | Aztec                       |
|                      | Codabar                     |
|                      | Code 128                    |
|                      | Code 39                     |
|                      | Code 93                     |
|                      | Composite Codes             |
|                      | Data Matrix Code            |
|                      | EAN 128                     |
|                      | EAN 8/13                    |
|                      | EAN Addendum                |
|                      | GS1 Databar                 |
|                      | GS1 Databar Expanded        |
|                      | GS1 Databar Limited         |
|                      | GS1 Databar Omnidirectional |
|                      | GS1 Databar Stacked         |
|                      | GS1 Databar Truncated       |
|                      | Maxicode                    |
|                      | Micro PDF                   |
|                      | Micro QR                    |
|                      | Others on request           |
|                      | PDF417                      |
|                      | QR code                     |
|                      | UPC                         |

### Optical data

|                               |               |
|-------------------------------|---------------|
| Reading distance              | 25 ... 596 mm |
| Camera resolution, horizontal | 838 px        |
| Camera resolution, vertical   | 640 px        |

### Electrical data

#### Performance data

|                          |           |
|--------------------------|-----------|
| Supply voltage $U_B$     | 3.7 V, DC |
| Power consumption, max.  | 1.8 W     |
| Battery technology       | Lilon     |
| Battery storage capacity | 2.4 A·h   |

### Interface

|      |                   |
|------|-------------------|
| Type | PS/2, RS 232, USB |
|------|-------------------|

### RS 232

|          |         |
|----------|---------|
| Function | Process |
|----------|---------|

### USB

|          |         |
|----------|---------|
| Function | Process |
|----------|---------|

### Connection

|                   |         |
|-------------------|---------|
| Bluetooth range   | Class 1 |
| Bluetooth version | 2.1     |

#### Connection 1

|                    |           |
|--------------------|-----------|
| Type of connection | Bluetooth |
|--------------------|-----------|

### Mechanical data

|                       |                         |
|-----------------------|-------------------------|
| Dimension (W x H x L) | 75 mm x 133 mm x 195 mm |
| Housing material      | Plastic                 |
| Plastic housing       | UL 94-V0                |
| Net weight            | 380 g                   |

### Environmental data

|                                    |                |
|------------------------------------|----------------|
| Ambient temperature, operation     | -20 ... 50 °C  |
| Ambient temperature, storage       | -40 ... 70 °C  |
| Relative humidity (non-condensing) | 0 ... 95 %     |
| Drop height                        | 2 m            |
| Measurements relative to           | Concrete floor |

### Certifications

|                      |       |
|----------------------|-------|
| Degree of protection | IP 65 |
|----------------------|-------|

### Classification

|                       |          |
|-----------------------|----------|
| Customs tariff number | 84719000 |
| eCl@ss 5.1.4          | 27280103 |
| eCl@ss 8.0            | 27280103 |
| eCl@ss 9.0            | 27280103 |
| eCl@ss 10.0           | 27280103 |
| eCl@ss 11.0           | 27280103 |
| ETIM 5.0              | EC002550 |
| ETIM 6.0              | EC002999 |
| ETIM 7.0              | EC002999 |

## Electrical connection

### Connection 1

|                    |                         |
|--------------------|-------------------------|
| Function           | Configuration interface |
|                    | Data interface          |
| Type of connection | Bluetooth               |



## Operation and display



| LED | Display               | Meaning            |
|-----|-----------------------|--------------------|
| 1   | Red, continuous light | Low battery level  |
|     | Green, 1x flashing    | Reading successful |


## Operation and display

| LED | Display       | Meaning             |
|-----|---------------|---------------------|
| 1   | Red, flashing | Communication error |

## Notes


|  <b>Observe intended use!</b> |   |
|--|---|
|                                | <ul style="list-style-type: none"> <li>⌘ This product is not a safety sensor and is not intended as personnel protection.</li> <li>⌘ The product may only be put into operation by competent persons.</li> <li>⌘ Only use the product in accordance with its intended use.</li> </ul> |

|  <b>WARNING! LASER RADIATION – CLASS 2 LASER PRODUCT</b> |   |
|---|---|
|   | <p><b>Do not stare into beam!</b><br/> <b>The device satisfies the requirements of IEC 60825-1:2007 (EN 60825-1:2007) safety regulations for a product of laser class 2 as well as the U.S. 21 CFR 1040.10 regulations with deviations corresponding to "Laser Notice No. 50" from June 24, 2007.</b></p> <ul style="list-style-type: none"> <li>⌘ Never look directly into the laser beam or in the direction of reflected laser beams! If you look into the beam path over a longer time period, there is a risk of injury to the retina.</li> <li>⌘ Do not point the laser beam of the device at persons!</li> <li>⌘ Interrupt the laser beam using a non-transparent, non-reflective object if the laser beam is accidentally directed towards a person.</li> <li>⌘ When mounting and aligning the device, avoid reflections of the laser beam off reflective surfaces!</li> <li>⌘ CAUTION! Use of controls or adjustments or performance of procedures other than specified herein may result in hazardous light exposure.</li> <li>⌘ Observe the applicable statutory and local laser protection regulations.</li> <li>⌘ The device must not be tampered with and must not be changed in any way.<br/>           There are no user-serviceable parts inside the device.<br/>           Repairs must only be performed by Leuze electronic GmbH + Co. KG.</li> </ul> |

| NOTE   |  |
|--|--|
|  | <p><b>Affix laser information and warning signs!</b><br/> <b>Laser information and warning signs are affixed to the device. In addition, self-adhesive laser information and warning signs (stick-on labels) are supplied in several languages.</b></p> <ul style="list-style-type: none"> <li>⌘ Affix the laser information sheet to the device in the language appropriate for the place of use. When using the device in the US, use the stick-on label with the "Complies with 21 CFR 1040.10" note.</li> <li>⌘ Affix the laser information and warning signs near the device if no signs are attached to the device (e.g. because the device is too small) or if the attached laser information and warning signs are concealed due to the installation position.</li> <li>⌘ Affix the laser information and warning signs so that they are legible without exposing the reader to the laser radiation of the device or other optical radiation.</li> </ul> |


## Accessories

### Connection technology - Connection unit

|  | Part no. | Designation              | Article                 | Description   |
|--|----------|--------------------------|-------------------------|---|
|  | 50112891 | MA 248i Profinet Gateway | Modular connection unit | Supply voltage: 18 ... 30 V<br>Current consumption, max.: 300 mA<br>Interface: PROFINET, RS 232<br>Connections: 6 Piece(s)<br>Degree of protection: IP 65 |


## Accessories

### Connection technology - Base stations



|  | Part no.   | Designation     | Article      | Description   |
|--|------------|-----------------|--------------|---|
|  | 50122431 * | Base f. IT 1911 | Base station | Interface: PS/2, USB, RS 232<br>Bluetooth range: Class 1<br>Bluetooth version: 2.1<br>Connection 1: RJ41<br>Connection 2: Jack socket<br>Connection 3: Bluetooth<br>Drop height: 1.2 m<br>Degree of protection: IP 51 |

\* Necessary accessories, please order separately

### Connection technology - Interconnection cables

|  | Part no. | Designation   | Article          | Description   |
|--|----------|---------------|------------------|---|
|  | 50113397 | KB JST-HS-300 | Connection cable | Suitable for interface: RS 232<br>Connection 1: JST ZHR<br>Connection 2: Sub-D, Axial, Male, 9 -pin<br>Shielded: Yes<br>Cable length: 300 mm<br>Sheathing material: PUR |

### Replacement part

|  | Part no.    | Designation       | Article | Description   |
|--|-------------|-------------------|---------|---|
|  | 50105384 ** | Battery IT-series | Battery | Supply voltage: 3.7 V, DC<br>Battery technology: Lilon<br>Battery storage capacity: 2.4 A·h |
|  | 50143603    | IT 19x1i-End Cap  | End cap | Type of fastening, at device: to engage   |

\*\* Included in delivery contents

#### Note



A list with all available accessories can be found on the Leuze website in the Download tab of the article detailed page.