

## Technical data sheet

### Connection cable

Part no.: 50130840

KD U-M8-3A-V1-150

#### Contents

- Technical data
- Electrical connection
- Circuit diagrams



Figure can vary



# Technical data

## Electrical data

### Performance data

Operating voltage 50 V AC / 60 V DC

## Connection

### Connection 1

|                      |  |
|----------------------|--|
| Type of connection   | Connector  |
| Thread size          | M8   |
| Type                 | Female   |
| Handle body material | PUR  |
| No. of pins          | 3 -pin   |
| Version              | Axial  |
| Lock                 | Screw fitting, nickel-plated diecast zinc, recommended torque 0.6 Nm, self-locking |

### Connection 2

Type of connection Open end

### Cable properties

|                                   |  |
|-----------------------------------|--|
| Number of conductors              | 3 Piece(s)   |
| Wire cross section                | 0.25 mm <sup>2</sup>   |
| AWG                               | 24   |
| Sheathing color                   | Black  |
| Shielded                          | No   |
| Silicone-free                     | Yes  |
| Cable design                      | Connection cable (open on one end)   |
| Cable diameter (external)         | 4.4 mm   |
| Cable length                      | 15,000 mm  |
| Sheathing material                | PVC  |
| Wire insulation                   | PVC  |
| Suitability for drag chains       | No   |
| Properties of the outer sheathing | Free of CFC, cadmium, silicone and lead, easily machine-processable                                  |
| Resistance of the outer sheathing | Good oil, gasoline and chemical resistance, flame retardant in accordance with UL 1581 VW1 / CSA FT1 |

## Mechanical data

|   |                          |
|---|--------------------------|
| Width across flats                      | 9 mm                     |
| Bending radius, flexible laying, min.   | Min. 10 x cable diameter |
| Bending radius, stationary laying, min. | Min. 5 x cable diameter  |

## Environmental data

|  |               |
|--|---------------|
| Ambient temperature, operation, flexible use   | -5 ... 80 °C  |
| Ambient temperature, operation, stationary use | -30 ... 80 °C |

## Certifications

|                      |         |
|----------------------|---------|
| Degree of protection | IP 65   |
|                      | IP 67   |
| Certifications       | c UL US |

## Classification

|                       |          |
|-----------------------|----------|
| Customs tariff number | 85444290 |
| eCl@ss 5.1.4          | 27279201 |
| eCl@ss 8.0            | 27279218 |
| eCl@ss 9.0            | 27060311 |
| eCl@ss 10.0           | 27060311 |
| eCl@ss 11.0           | 27060311 |
| ETIM 5.0              | EC001855 |
| ETIM 6.0              | EC001855 |
| ETIM 7.0              | EC001855 |

# Electrical connection


## Connection 1

|                      |  |
|----------------------|--|
| Type of connection   | Connector  |
| Thread size          | M8   |
| Type                 | Female   |
| Handle body material | PUR  |
| No. of pins          | 3 -pin   |
| Version              | Axial  |
| Lock                 | Screw fitting, nickel-plated diecast zinc, recommended torque 0.6 Nm, self-locking |

## Pin

|   |       |
|---|-------|
| 1 | Brown |
| 3 | Blue  |
| 4 | Black |

## Conductor color



## Electrical connection

### Connection 2

Type of connection

Open end

## Circuit diagrams

### Wiring schematic

