

Technical data sheet

Distribution box

Part no.: 50130993

MD 7XXP-11-108IO3-12

Contents

- Technical data
- Dimensioned drawings
- Electrical connection
- Circuit diagrams
- Operation and display
- Accessories



Figure can vary



Technical data

Electrical data

Switching signal	PNP
------------------	-----

Performance data

Total current	1.5 A
---------------	-------

Input data logic

Nominal input voltage U_N	24 V DC
-----------------------------	---------

Connection

Master connection

Type of connection	Connector
--------------------	-----------

Function	Connection to the control
----------	---------------------------

Thread size	M12
-------------	-----

No. of pins	12 -pin
-------------	---------

Encoding	A-coded
----------	---------

Type	Male
------	------

Distribution box connections

Number of connections	10 Piece(s)
-----------------------	-------------

Thread size	M8
-------------	----

No. of pins	3 -pin
-------------	--------

Encoding	A-coded
----------	---------

Type	Female
------	--------

Material	Plastic
----------	---------

Material of O-ring seal	TPU
-------------------------	-----

Material of contacts	Gold-plated
----------------------	-------------

Operating current per contact	1.5 A
-------------------------------	-------

Mechanical data

Design	Cubic
--------	-------

Dimension (W x H x L)	30 mm x 31.5 mm x 150 mm
-----------------------	--------------------------

Housing material	Plastic
------------------	---------

Net weight	149 g
------------	-------

Screw tightening torque	0 N·m
-------------------------	-------

Operation and display

Type of display	LED
-----------------	-----

Environmental data

Ambient temperature, operation	-20 ... 70 °C, Depending on the connected cable
--------------------------------	---

Certifications

Degree of protection	IP 65
----------------------	-------

IP 67

Certifications	c UL US
----------------	---------

Classification

Customs tariff number	85369010
-----------------------	----------

eCl@ss 5.1.4	27279201
--------------	----------

eCl@ss 8.0	27279219
------------	----------

eCl@ss 9.0	27440108
------------	----------

eCl@ss 10.0	27440108
-------------	----------

eCl@ss 11.0	27440108
-------------	----------


ETIM 5.0	EC002585
----------	----------

ETIM 6.0	EC002585
----------	----------

ETIM 7.0	EC002585
----------	----------


Dimensioned drawings

All dimensions in millimeters




Electrical connection


Pin	Pin assignment	Conductor color
1	Socket 1-10 / contact 1	Brown
2	Socket 1-10 / contact 3	Blue
3	Socket 1 / contact 4	White
4	Socket 2 / contact 4	Green
5	Socket 5 / contact 4	Pink
6	Socket 3 / contact 4	Yellow
7	Socket 7 / contact 4	Black
8	Socket 4 / contact 4	Gray
9	Socket 6 / contact 4	Red
10	Socket 8 / contact 4	Violet
11	Socket 9 / contact 4	Gray
		Pink
12	Socket 10 / contact 4	Blue
		Red



Pin	Pin assignment	Conductor color
1	+	Brown
3	-	Blue
4	S1	See table above



Circuit diagrams



Operation and display

LED	Display	Meaning
1	Green, continuous light	Operating voltage applied
2	Yellow, continuous light	Signal 1


Accessories

Connection technology - Connection cables

	Part no.	Designation	Article	Description
	50139769	KD U-M12-CA-P1-020	Connection cable	Connection 1: Connector, M12, Axial, Female, A-coded, 12 -pin Connection 2: Open end Shielded: No Cable length: 2,000 mm Sheathing material: PUR
	50139770	KD U-M12-CA-P1-050	Connection cable	Connection 1: Connector, M12, Axial, Female, A-coded, 12 -pin Connection 2: Open end Shielded: No Cable length: 5,000 mm Sheathing material: PUR
	50139771	KD U-M12-CA-P1-100	Connection cable	Connection 1: Connector, M12, Axial, Female, A-coded, 12 -pin Connection 2: Open end Shielded: Yes Cable length: 2,000 mm Sheathing material: PUR

Accessories

General

	Part no.	Designation	Article	Description
	50134479	CAP M8K-Set	Connection cap	Type: Cap for free sockets Thread size: M8 Material: Plastic

Note



A list with all available accessories can be found on the Leuze website in the Download tab of the article detailed page.